

UltraClean BlenD™

*Simplify sustainability with
a better blend.*

UltraClean BlenD™ is a proprietary fuel that combines renewable diesel and biodiesel to help you meet low carbon goals simply—with no infrastructure changes.




Superior performance.

UltraClean BlenD™ provides excellent lubricity, high Cetane, and low Cloud Point for superior performance, all while enabling sustainability targets to be met.



Superior lubricity to renewable diesel and can even have a lower freezing point



Carbon Intensity (CI) scores that are much lower than petroleum diesel allow for decarbonization today



UltraClean Blend™ can provide the lowest overall engine emissions of any diesel fuel option



Elastomer swell, density and bulk modulus properties of UltraClean Blend™ are a better match for conventional diesel than 100% renewable diesel

UltraClean Blend™

UltraClean Blend™ is a proprietary, 100% renewable fuel combination of VelociD™ and PuriD™ that allows decarbonization today in virtually any diesel application.

Our focus is on your success.

For more than 25 years, we've helped industries implement practical solutions to complex sustainability challenges by providing leading-edge quality, go-to-market agility, sustainable partnerships and sensible decarbonization strategies.

For more information

North America: Contact Renewable Energy Group at 844.405.0160 or connect with us at [regi.com](https://www.regi.com)

Europe: Contact REG at +31 20 757 6800 or eur-sales@regi.com

REGI.COM



Renewable Energy Group proudly reproduces on paper containing recycled materials.

Renewable Energy Group, REG, the logo and the other trademarks and trade names referenced herein are trademarks of Chevron U.S.A. Inc.

© 2022 Chevron U.S.A. All Rights Reserved.

The information contained herein is believed to be reliable but REG makes no representations concerning the accuracy or correctness of the data. These products, like any other should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary.

