

Beyond™

A sustainable aviation fuel blendstock that's leading the way.

Part of Chevron Renewable Energy Group's complete EnDura Fuels™ product line, is a high-quality sustainable aviation fuel blendstock that meets specifications and reduces lifecycle carbon emissions compared to petroleum jet fuel.



Performance beyond expectations.

From Chevron Renewable Energy Group, a leading bio-based fuel producer, Beyond™ makes a lower-carbon future possible for the aviation industry.





Meets the ASTM D7566 fuel specification



Produced with no fossil carbon, allowing notable reductions in direct aircraft fossil carbon emissions on a lifecycle basis¹



Lower carbon intensity blendstock for petroleum jet fuel

Beyond[™]

Beyond[™] is a lower-carbon sustainable aviation fuel (SAF) blendstock that will help lead the way in emissions solutions for the aviation industry.

¹ Product is produced from renewable oils and fats. Methanol used to make biodiesel and hydrogen used to make renewable diesel and SAF are typically made from conventional natural gas but can be produced from renewable resources.

Our focus is on your success.

For more than 25 years, we've helped industries implement practical solutions to complex sustainability challenges by providing leading-edge quality, go-to-market agility, strategic partnerships and sensible lower-carbon solutions.

For more information

North America: Contact Chevron Renewable Energy Group at 844.405.0160 or connect with us at regi.com

Europe: Contact Chevron Renewable Energy Group at +31 20 757 6800 or eur-sales@regi.com

REGI.COM

 Chevron Renewable Energy Group proudly reproduces on paper containing recycled materials.

Renewable Energy Group, REG, the logo and the other trademarks and trade names referenced herein are trademarks of Chevron U.S.A. Inc.
© 2023 Chevron U.S.A. All Rights Reserved.

The information contained herein is believed to be reliable but Chevron Renewable Energy Group makes no representations concerning the accuracy or correctness of the data. These products, like any other should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary.

